

**Oxygen High Pressure Flexible Hose with Heatsink & Ceramic** Non-Return Valve



The Lab Master LGF520 high pressure flexible hoses are designed for use with Oxygen up to grade 5.0 purity (99.999%). They are intended for use in conjunction with our gas control panels.

LGF520 | Oxygen High Pressure Flexible Hose with Heatsink & Ceramic Non-Return Valve

## FEATURES

- Ceramic Non-Return Valve (NRV)
- 1/4" NPT Female Inlet
- 1/4" NPT Male Outlet from NRV
- Anti-Whip

#### MATERIAL

- Hose Fittings
- Stainless Steel Braided Nickel Plated Brass

### 🖒 SPECIFICATION

- Maximum Working Pressure
- Temperature Range Weight
- 300 bar (4350 PSI) -40° C to +100° C (-5° F to +212° F)
- 1.0 kg (2.20 lb) 900 mm typical

# <sup>1</sup><sup>2</sup> MODEL NO. SELECTOR GUIDE

#### Example for a Model No. for LGF520 Series

LGF520-	04-	02-	01-	00-	000-	04-	Α
Product Type	Inlet Pressure Bar [PSI]	Length	Non Return Valve	Colour	Inlet/ Cylinder Connection	Outlet	Options
LGF520	<b>04</b> 300 [4350]	<b>02</b> 900 mm	01 NRV fitted	00 No options	000 1/4 NPT Female	04 1/4 NPT Male	A No Options Selected
		<b>03</b> 1800 mm			010 BS341 No.3		K Certificate of Conformity
					012 BS341 No.4		P Calibration / Pressure Test Certificate
					other connetions available, please refer to the data sheet "Cylinder connection"		



Headoffice / Factory UK Gas-Arc Group Limited Vinces Road | Diss | Norfolk | IP22 4WW | UK t: +44 (0) 1379 652263 | f: +44 (0) 1379 644235

#### **Office Germany**

Gas-Arc Aegidienstraße 12 | 23552 Lübeck | Germany t: +49 (0) 451 790 77 543

We do everything we can to ensure that the technical information within this document is correct at time of publishing, however content may be changed without notice.