

Stainless Steel Spiral High Pressure Flexible Tailpipe with Ceramic Non-Return Valve





- Ceramic Non-Return Valve (NRV)
- 1/4" NPT Female Inlet
- 1/4" NPT Male Outlet from NRV
- Orbitally welded: 1/4 NPT fitting
- Anti-Whip Safety Feature



Coiled Stainless Tube Tubing 316L Stainless Steel Fittings

The Spec Master HPF650 high pressure flexible tailpipes are designed for use with noncorrosive or toxic, high purity gases up to grade 6.0 purity (99.9999%). They are intended for use in conjunction with our gas control panels.

■ HPF650 | Stainless Steel Spiral High Pressure Flexible Tailpipe with Ceramic Non-Return Valve

SPECIFICATION

300 bar (4350 PSI) Maximum Working Pressure

■ Temperature Range -40° C to +60° C (-5° F to +140° F)

■ Weight 1.0 kg (2.20 lb) Helium Leak Integrity 1x10⁻⁹ mbar I/s

2 MODEL NO. SELECTOR GUIDE

Example for a Model No. for HPF650

HPF650-	04-	01-	01	00	000-	00	Α
Product Type	Inlet Pressure Bar [PSI]	Length	Non Return Valve	Colour	Inlet/ Cylinder Connection	Outlet	Options
HPF650	04 300 [4350]	01 600 mm	01 NRV fitted	00 Stainless Steel Finish no further options	000 1/4 NPT Female	04 1/4 NPT Male	A No Options Selected
					010 BS341 No.3		K Certificate of Conformity
					012 BS341 No.4		P Calibration / Pressure Test Certificate
					other connections available, please refer to the data sheet "Cylinder connection"		



Headoffice / Factory UK Gas-Arc Group Limited

Vinces Road | Diss | Norfolk | IP22 4WW | UK t: +44 (0) 1379 652263 | f: +44 (0) 1379 644235 Office Germany

Aegidienstraße 12 | 23552 Lübeck | Germany t: +49 (0) 451 790 77 543