

Cupro/Nickel High Pressure Flexible Tailpipe with Ceramic Non-Return Valve





- Ceramic Non-Return Valve (NRV)
- 1/4" NPT Female Inlet
- 1/4" NPT Male Outlet from NRV

# MATERIAL

Cupro/Nickel Tailpipe

Brass ■ Fittings

The Tech Master GPF430 high pressure flexible tailpipes are designed for use with noncorrosive or toxic, technical gases up to grade 4.5 purity (99.995%). They are intended for use in conjunction with our gas control panels.

■ GPF430 | Cupro/Nickel High Pressure Flexible Tailpipe with Ceramic Non-Return Valve

# **SPECIFICATION**

Maximum Working Pressure 300 bar (4350 PSI)

■ Temperature Range -20° C to +60° C (-4° F to +140° F)

# <sup>1</sup>2 MODEL NO. SELECTOR GUIDE

## Example for a Model No. for GPF430 Series

GPF430-	04-	02-	01-	00-	000-	04-	Α
Product Type	Inlet Pressure Bar [PSI]	Length	Non Return Valve	Colour	Inlet/ Cylinder Connection	Outlet	Options
GPF430	<b>04</b> 300 [4350]	<b>01</b> 600 mm	01 NRV fitted	00 No options	000 1/4 NPT Female	<b>04</b> 1/4 NPT Male	A No Options Selected
		<b>02</b> 900 mm			<b>010</b> BS341 No.3		K Certificate of Conformity
		<b>03</b> 1800 mm			<b>012</b> BS341 No.4		P Calibration / Pressure Test Certificate
					other connetions available, please refer to the data sheet "Cylinder connection"		



**Headoffice / Factory UK** Gas-Arc Group Limited

Vinces Road | Diss | Norfolk | IP22 4WW | UK t: +44 (0) 1379 652263 | f: +44 (0) 1379 644235

### Office Germany

Gas-Arc

Aegidienstraße 12 | 23552 Lübeck | Germany

t: +49 (0) 451 790 77 543