

Tech Master – GPF410

Acetylene High Pressure Flexible Hose with EPDM Non-Return Valve



The Tech Master GPF410 high pressure flexible hoses are designed for use with technical Acetylene up to grade 4.5 (99.995%). They are intended for use in conjunction with our gas control panels.

■ **GPF410** | Hose with EPDM Non-Return Valve for Acetylene

★ FEATURES

- EPDM Non-Return Valve (NRV)
- 1/4" NPT Male Outlet from NRV
- 1/4 BSP female loose running nut – Inlet
- Anti-Whip

📁 MATERIAL

- **Hose** Braided with protective cover
EN ISO14113
Acetylene Decomposition Tested
- **Fittings** Brass

👍 SPECIFICATION

- **Maximum Working Pressure** 25 bar (360 PSI)
- **Temperature Range** -20° C to +60° C (-4° F to +140° F)
- **Weight** 1.0 kg (2.20 lb) 900 mm typical

1 2 3 MODEL NO. SELECTOR GUIDE

Example for a Model No. for GPF410 Series

GPF410-	01-	02-	01-	00-	000-	04-	A
Product Type	Inlet Pressure Bar [PSI]	Length	Non Return Valve	Colour	Inlet/ Cylinder Connection	Outlet	Options
GPF410	01 25 [360]	02 900 mm	01 NRV fitted	00 No options	000 1/4 NPT Female	04 1/4 NPT Male	A No Options Selected
		03 1800 mm			010 BS341 No.3		K Certificate of Conformity
					012 BS341 No.4		P Calibration / Pressure Test Certificate
					other connetions available, please refer to the data sheet "Cylinder connection"		